



maxsonTM

ADHESIVE



MFG. OF PVC | UPVC | CPVC ADHESIVE



Makers by :
Solvo-Weld Adhesives India Pvt. Ltd.



maxsonTM
ADHESIVE



UPVC CEMENT

PRODUCT DETAILS:

Brand	FastoWeld
Surface of Application	Plastic
Form	Liquid
Specific Gravity	0.900 - 0.900 gm/cm ³
Boiling Point	85 Degree C
Odour	Strong
Grade Standard	Chemical Grade
Curing Time	35 Minutes
Pipe Joining Time	2.0 Minutes
Solid Content	Min. 12% by mass

No.	SIZE	Rate	Inner Packing	Master Packing
1	10 ml	18	144 (Tube)	1152
2	25 ml	30	96 (Tube)	768
3	50 ml	70	50 (Tin) With Brush	400
4	118 ml	125	24 (Tin) With Brush	288
5	237 ml	240	16 (Tin) With Brush	128
6	500 ml	430	12 (Tin) With Brush	96
7	1 Ltr.	800	6 (Tin) With Brush	42

Features:

- High pot life
- Ensure leak proof joining but extra strong bonding capacity
- Resistance against adverse weathering conditions

Self Life

- 24 months in tightly sealed containers. Manufacturer date is printed on the bottom of the container.



maxsonTM
ADHESIVE



UPVC CEMENT

PRODUCT DETAILS:

Brand	FastoWeld
Surface of Application	Plastic
Form	Liquid
Specific Gravity	0.900 - 0.900 gm/cm ³
Boiling Point	85 Degree C
Odour	Strong
Grade Standard	Chemical Grade
Curing Time	35 Minutes
Pipe Joining Time	2.0 Minutes
Solid Content	Min. 12% by mass

No.	SIZE	Rate	Inner Packing	Master Packing
1	10 ml	15	144 (Tube)	1152
2	25 ml	25	96 (Tube)	768
3	50 ml	55	50 (Tin) With Brush	400
4	118 ml	100	24 (Tin) With Brush	288
5	237 ml	175	16 (Tin) With Brush	128
6	500 ml	320	12 (Tin) With Brush	96
7	1 Ltr.	450	6 (Tin) With Brush	42

Features:

- High pot life
- Ensure leak proof joining but extra strong bonding capacity
- Resistance against adverse weathering conditions

Self Life

- 24 months in tightly sealed containers. Manufacturer date is printed on the bottom of the container.



maxson™
ADHESIVE



PVC CEMENT

PRODUCT DETAILS:

Brand	FastoWeld
Packaging Type	Tube, Can
Form	Clear Transparent Liquid
Surface of Application	Plastic
Specific Gravity	0.850 - 0.900 gm/cm3
Odour	Strong
Curing Time	35 Minutes
Pipe Joining Time	2 Minutes
Solid Content	10% by mass
Used for	joining of ISI PVC pipes and PVC fittings

No.	SIZE	Rate	Inner Packing	Master Packing
1	10 ml	13	144 (Tube)	1152
2	25 ml	20	96 (Tube)	768
3	50 ml	40	50 (Tin) With Brush	400
4	100 ml	55	24 (Tin) With Brush	288
5	237 ml	110	16 (Tin) With Brush	128
6	500 ml	185	12 (Tin) With Brush	96
7	1 Ltr.	350	6 (Tin) With Brush	42

Features:

- High pot life
- Ensure leak proof joining but extra strong bonding capacity
- Resistance against adverse weathering conditions

Self Life

- 24 months in tightly sealed containers. Manufacturer date is printed on the bottom of the container.



Makers by :

Solvo-Weld Adhesives India Pvt. Ltd.

Plot No. 17, N.K. Industrial Park-1, Bakrol-Bujrang Village, Ta. Daskroi, Dist. A'bad.

sales@solvoweldadhesive.com | info@solvoweldadhesive.com

C.C NO. 6355 428 641